



NONWOVEN MICROPORUS FILM LAMINATED (68 gram)
COMPOSITION: 52% POLYPROPYLENE 48% POLYETHYLENE

PERFORMANCE AGAINST CHEMICALS: ASTM F101

CHEMICAL	PENETRATION RESULTS	BREAKTHROUGH (min.)	RATE (min.)
ACETONE	PASS	8	0.62
ACETONITRILE	PASS	< 4	8.7
AMMONIA	NT	4	4.5
1,3-BUTADIENE	NT	8	11.9
CARBON DISULFIDE	PASS	< 4	< 50
CHLORINE	NT	6	23
DICHLOROMETHANE	PASS	4	0.59
DIETHYLAMINE	PASS	4	9.5
DIMETHYL FORMAMIDE	PASS	8	2.1
ETHYL ACETATE	PASS	4	3.3
ETHYLENE OXIDE	NT	< 4	359

^{*}This image is representative and may vary from actual product.



PERFORMANCE AGAINST CHEMICALS: ASTM F101

PROGARDTEX 70

CHEMICAL	PENETRATION RESULTS	BREAKTHROUGH (min.)	RATE (min.)
N-HEXANE	PASS	4	6.3
HYDROGEN CHLORIDE	NT	30	< 50
METHANOL	PASS	< 4	2.23
METHYL CHLORIDE	NT	4	0.38
NITROBENZENE	PASS	4	16
SODIUM HYDROXIDE	PASS	ND	ND
SULFURIC ACID	PASS	ND	ND
TETRACHLOROETHYLENE	PASS	8	10
TETRAHYDROFURAN	PASS	< 4	< 50
TOLUENE	PASS	8	25

^{*}This image is representative and may vary from actual product.



PHYSICAL PROPERTIES	METHOD	UNIT	RESULT
BASIS WEIGHT	ASTM D3776	Oz/y²	1.7
TENSILE STRENGTH	ASTM D5034	Lb./in- MD Lb./in -CD	29.2 24.6
ELONGATION	ASTM D5034	% MD % CD	54.6 70.1
TRAPEZOIDAL TEAR	ASTM D5733	Lb./in- MD Lb./in -CD	12.4 10.8
HYDRAULIC BURSTING STRENGTH	ASTM D3786-87	Psi	34.8
HYDROSTATIC PRESSURE	AATCC 127-1994	Mbar	>100
WATER VAPOR TRANSMISSION RATE (50% RH @ 90°F)	ASTM E96	Grs/m2/24hrs	65
STATIC DECAY	NFPA 99	<0.5 SEC	PASS
BLOOD PENETRATION	ASTM F1670	PROCEDURE B	PASS
PENETRATION BY BLOOD-BORNE PATHOGENS	ASTM F1671	PROCEDURE B	PASS
PENETRATION BY LIQUIDS	ASTM F903	2 Psi	PASS
PERMEATION OF LIQUIDS AND GASES	ASTM F739	>1 mm Hg at 25 °C	PASS
LINTING	HELMKE DRUM	PARTIC/MIN >0.5 MM	585
RESISTANCE TO PUNCTURE	ASTM F1342-91	LBS	1.1

^{*}This image is representative and may vary from actual product.





NONWOVEN MICROPORUS FILM LAMINATED (68 gram)
COMPOSITION: 52% POLYPROPYLENE 48% POLYETHYLENE

MODEL
4001

BASIC
COVERALL

Description:

- · BASIC COVERALL
- · NO ELASTICS
- · FRONTAL PLASTIC ZIPPER 28"
- · SERGED SEAMS

- · SIZES: S 4XL
- **PCS / CASE**: 25
- · WEIGHT / CASE: 7 LB
- · **DESIGN**: ANSI
- · COLOR:



Main Features:


- · WATERPROOF Provides a 100% barrier against liquids.
- ANTI-STATIC Passes NFPA 99 for antistatic materials.
- LIQUID AND PARTICULATE BARRIER
 Protection against 0.3 0.5 micron particles.
- LIQUIDS UNDER PRESSURE RESISTANT Better liquid barrier than Tyvek.
- PROTECTS AGAINST BLOOD AND BODY FLUIDS Passes ASTM F1670.
- · Meets ANSI/ISEA 101-1996 sizing standards.

Main Uses:

- · General Maintenance
- · Medical & Pharmaceutical
- · Food processing
- Laboratories
- Veterinary
- · Light chemical handling
- · Pest Control
- Automotive
- Asbestos
- Fiberglass
- · Clean rooms

^{*}This image is representative and may vary from actual product.





NONWOVEN MICROPORUS FILM LAMINATED (68 gram)
COMPOSITION: 52% POLYPROPYLENE 48% POLYETHYLENE

MODEL
4002
ELASTICATED
CUFF & ANKLES
COVERALL

Description:

- · COVERALL
- · ELASTIC IN WRISTS AND ANKLES
- · FRONTAL PLASTIC ZIPPER 28"
- · SERGED SEAMS

- **SIZES**: S 4XL **PCS / CASE**: 25
- · WEIGHT / CASE: 7 LB
- · **DESIGN**: ANSI
- · COLOR:



Main Features:


- WATERPROOF Provides a 100% barrier against liquids.
- · ANTI-STATIC Passes NFPA 99 for antistatic materials.
- LIQUID AND PARTICULATE BARRIER
 Protection against 0.3 0.5 micron particles.
- LIQUIDS UNDER PRESSURE RESISTANT Better liquid barrier than Tyvek.
- PROTECTS AGAINST BLOOD AND BODY FLUIDS Passes ASTM F1670.
- · Meets ANSI/ISEA 101-1996 sizing standards.

Main Uses:

- · General Maintenance
- · Medical & Pharmaceutical
- Food processing
- Laboratories
- Veterinary
- · Light chemical handling
- · Pest Control
- Automotive
- Asbestos
- Fiberglass
- · Clean rooms

^{*}This image is representative and may vary from actual product.





NONWOVEN MICROPORUS FILM LAMINATED (68 gram)
COMPOSITION: 52% POLYPROPYLENE 48% POLYETHYLENE

MODEL
4003
HOODED
COVERALL

Description:

- · HOODED COVERALL
- · ELASTICS IN WRISTS AND ANKLES
- · FRONTAL PLASTIC ZIPPER 28"
- · SERGED SEAMS

- **SIZES:** S 4XL
- PCS / CASE: 25 • WEIGHT / CASE: 8 LB
- · **DESIGN**: ANSI
- · COLOR:



Main Features:


- WATERPROOF Provides a 100% barrier against liquids.
- ANTI-STATIC Passes NFPA 99 for antistatic materials.
- LIQUID AND PARTICULATE BARRIER
 Protection against 0.3 0.5 micron particles.
- LIQUIDS UNDER PRESSURE RESISTANT Better liquid barrier than Tyvek.
- PROTECTS AGAINST BLOOD AND BODY FLUIDS Passes ASTM F1670.
- · Meets ANSI/ISEA 101-1996 sizing standards.

Main Uses:

- · General Maintenance
- · Medical & Pharmaceutical
- Food processing
- Laboratories
- Veterinary
- · Light chemical handling
- · Pest Control
- Automotive
- Asbestos
- Fiberglass
- · Clean rooms

^{*}This image is representative and may vary from actual product.





NONWOVEN MICROPORUS FILM LAMINATED (68 gram)
COMPOSITION: 52% POLYPROPYLENE 48% POLYETHYLENE

MODEL
4004
HOODED
COVERALL WITH
BOOTS

Description:

- · HOODED COVERALL WITH BOOTS
- · ELASTICS IN WRISTS AND ANKLES
- · FRONTAL PLASTIC ZIPPER 28"
- · SERGED SEAMS

• **SIZES**: S - 4XL • **PCS / CASE**: 25

· WEIGHT / CASE: 10 LB

· **DESIGN**: ANSI

· COLOR:



Main Features:


- WATERPROOF Provides a 100% barrier against liquids.
- ANTI-STATIC Passes NFPA 99 for antistatic materials.
- LIQUID AND PARTICULATE BARRIER
 Protection against 0.3 0.5 micron particles.
- LIQUIDS UNDER PRESSURE RESISTANT Better liquid barrier than Tyvek.
- PROTECTS AGAINST BLOOD AND BODY FLUIDS Passes ASTM F1670.
- · Meets ANSI/ISEA 101-1996 sizing standards.

Main Uses:

- · General Maintenance
- · Medical & Pharmaceutical
- · Food processing
- Laboratories
- Veterinary
- · Light chemical handling
- · Pest Control
- Automotive
- Asbestos
- Fiberglass
- · Clean rooms

^{*}This image is representative and may vary from actual product.





NONWOVEN MICROPORUS FILM LAMINATED (68 gram)
COMPOSITION: 52% POLYPROPYLENE 48% POLYETHYLENE

MODEL
4010
SLEEVE COVER

Description:

- · SLEEVE COVER
- 18" LONG
- · ELASTIC WRIST AND ARM

· SIZES: ONE SIZE

• **PCS / CASE:** 200 = 100 PAIRS

· WEIGHT / CASE: 4 LB

· **DESIGN**: ANSI

· COLOR:



Main Features:


- WATERPROOF Provides a 100% barrier against liquids.
- ANTI-STATIC Passes NFPA 99 for antistatic materials.
- LIQUID AND PARTICULATE BARRIER
 Protection against 0.3 0.5 micron particles.
- LIQUIDS UNDER PRESSURE RESISTANT Better liquid barrier than Tyvek.
- PROTECTS AGAINST BLOOD AND BODY FLUIDS Passes ASTM F1670.
- · Meets ANSI/ISEA 101-1996 sizing standards.

Main Uses:

- · General Maintenance
- · Medical & Pharmaceutical
- · Food processing
- Laboratories
- Veterinary
- · Light chemical handling
- · Pest Control
- Automotive
- Asbestos
- Fiberglass
- · Clean rooms

^{*}This image is representative and may vary from actual product.





NONWOVEN MICROPORUS FILM LAMINATED (68 gram)
COMPOSITION: 52% POLYPROPYLENE 48% POLYETHYLENE

MODEL 4017
SHOE COVER

Description:

- · SHOE COVER
- · ELASTIC ANKLES

- · SIZES: ONE SIZE
- **PCS / CASE:** 200 = 100 PAIRS
- · WEIGHT / CASE: 6 LB
- · **DESIGN**: ANSI
- · COLOR:



Main Features:


- WATERPROOF Provides a 100% barrier against liquids.
- · ANTI-STATIC Passes NFPA 99 for antistatic materials.
- LIQUID AND PARTICULATE BARRIER
 Protection against 0.3 0.5 micron particles.
- LIQUIDS UNDER PRESSURE RESISTANT Better liquid barrier than Tyvek.
- PROTECTS AGAINST BLOOD AND BODY FLUIDS Passes ASTM F1670.
- · Meets ANSI/ISEA 101-1996 sizing standards.

Main Uses:

- · General Maintenance
- · Medical & Pharmaceutical
- Food processing
- Laboratories
- Veterinary
- · Light chemical handling
- · Pest Control
- Automotive
- Asbestos
- Fiberglass
- · Clean rooms

^{*}This image is representative and may vary from actual product.





NONWOVEN MICROPORUS FILM LAMINATED (68 gram)
COMPOSITION: 52% POLYPROPYLENE 48% POLYETHYLENE

MODEL
4018
BOOT COVER

Description:

- · BOOT COVER
- · 14" TALL
- · ELASTIC LEG OPENING

· SIZES: ONE SIZE

• **PCS / CASE:** 200 = 100 PAIRS

· WEIGHT / CASE: 10 LB

· **DESIGN**: ANSI

· COLOR:

Main Uses:


Main Features:

- · WATERPROOF Provides a 100% barrier against liquids.
- ANTI-STATIC Passes NFPA 99 for antistatic materials.
- LIQUID AND PARTICULATE BARRIER
 Protection against 0.3 0.5 micron particles.
- LIQUIDS UNDER PRESSURE RESISTANT Better liquid barrier than Tyvek.
- PROTECTS AGAINST BLOOD AND BODY FLUIDS Passes ASTM F1670.
- · Meets ANSI/ISEA 101-1996 sizing standards.

- · General Maintenance
- · Medical & Pharmaceutical
- · Food processing
- Laboratories
- Veterinary
- · Light chemical handling
- · Pest Control
- Automotive
- Asbestos
- Fiberglass
- · Clean rooms

^{*}This image is representative and may vary from actual product.





NONWOVEN MICROPORUS FILM LAMINATED (68 gram)
COMPOSITION: 52% POLYPROPYLENE 48% POLYETHYLENE

MODEL
4019
NONSKID BOOT
COVER

Description:

- · NONSKID BOOT COVER
- · VINYL SOLE
- · 19" TALL
- · ELASTIC ANKLES AND LEG OPENING

- · SIZES: ONE SIZE
- PCS / CASE: 200 = 100 PAIRS
- · WEIGHT / CASE: 12 LB
- · **DESIGN**: ANSI
- · COLOR:



Main Features:

- WATERPROOF Provides a 100% barrier against liquids.
- · ANTI-STATIC Passes NFPA 99 for antistatic materials.
- LIQUID AND PARTICULATE BARRIER
 Protection against 0.3 0.5 micron particles.
- LIQUIDS UNDER PRESSURE RESISTANT Better liquid barrier than Tyvek.
- PROTECTS AGAINST BLOOD AND BODY FLUIDS Passes ASTM F1670.
- · Meets ANSI/ISEA 101-1996 sizing standards.

Main Uses:

- · General Maintenance
- · Medical & Pharmaceutical
- Food processing
- Laboratories
- Veterinary
- · Light chemical handling
- · Pest Control
- Automotive
- Asbestos
- Fiberglass
- · Clean rooms

^{*}This image is representative and may vary from actual product.





NONWOVEN MICROPORUS FILM LAMINATED (68 gram)
COMPOSITION: 52% POLYPROPYLENE 48% POLYETHYLENE

MODEL 4020 LAB COAT

Description:

- · LAB COAT
- · NO POCKETS
- · NO ELASTICS (WRISTS OPTIONAL)
- · THREE FRONT SNAP CLOSURES
- · SERGED SEAMS

· SIZES: S - 4XL

• **PCS / CASE**: 30

· WEIGHT / CASE: 6 LB

· **DESIGN**: ANSI

· COLOR:



Main Features:

- WATERPROOF Provides a 100% barrier against liquids.
- · ANTI-STATIC Passes NFPA 99 for antistatic materials.
- LIQUID AND PARTICULATE BARRIER
 Protection against 0.3 0.5 micron particles.
- LIQUIDS UNDER PRESSURE RESISTANT Better liquid barrier than Tyvek.
- PROTECTS AGAINST BLOOD AND BODY FLUIDS Passes ASTM F1670.
- · Meets ANSI/ISEA 101-1996 sizing standards.

Main Uses:

- · General Maintenance
- · Medical & Pharmaceutical
- Food processing
- Laboratories
- Veterinary
- · Light chemical handling
- · Pest Control
- Automotive
- Asbestos
- Fiberglass
- · Clean rooms

^{*}This image is representative and may vary from actual product.



STYLE	DESCR	IMAGE	
4001	BASIC COVERALL NO ELASTICS FRONTAL ZIPPER 28" SERGED SEAMS	· SIZES: S - 4XL · PCS / CASE: 25 · WEIGHT / CASE: 7 LB · DESIGN: ANSI · COLOR: WHITE, GRAY, YELLOW & ORANGE	
4002	COVERALL, ELASTIC WRISTS AND ANKLES FRONTAL ZIPPER 28" SERGED SEAMS	· SIZES: S - 4XL · PCS / CASE: 25 · WEIGHT / CASE: 7 LB · DESIGN: ANSI · COLOR: WHITE, GRAY, YELLOW & ORANGE	
4003	HOODED COVERALL, ELASTIC WRISTS AND ANKLES FRONTAL ZIPPER 28" SERGED SEAMS	· SIZES: S - 4XL · PCS / CASE: 25 · WEIGHT / CASE: 8 LB · DESIGN: ANSI · COLOR: WHITE, GRAY, YELLOW & ORANGE	

^{*}This image is representative and may vary from actual product.



STYLE	DESCRPITION		IMAGE
4004	HOODED COVERALL WITH BOOTS ELASTIC WRISTS AND ANKLES FRONTAL ZIPPER 28" SERGED SEAMS	· SIZES: S - 4XL · PCS / CASE: 25 · WEIGHT / CASE: 10 LB · DESIGN: ANSI · COLOR: WHITE, GRAY, YELLOW & ORANGE	
4010	SLEEVE COVER 18" LONG ELASTIC: WRISTS AND ARM	· SIZES: ONE SIZE · PCS / CASE: 200 = 100 PAIRS · WEIGHT / CASE: 4 LB · DESIGN: ANSI · COLOR: WHITE, GRAY, YELLOW & ORANGE	
4017	SHOE COVER ELASTIC ANKLE	• SIZES: ONE SIZE • PCS / CASE: 200 = 100 PAIRS • WEIGHT / CASE: 6 LB • DESIGN: ANSI • COLOR: WHITE, GRAY, YELLOW & ORANGE	

^{*}This image is representative and may vary from actual product.



STYLE	DESCF	IMAGE	
4018	BOOT COVER 14" TALL ELASTIC LEG OPENING	· SIZES: ONE SIZE · PCS / CASE: 200 = 100 PAIRS · WEIGHT / CASE: 10 LB · DESIGN: ANSI · COLOR: WHITE, GRAY, YELLOW & ORANGE	
4019	NONSKID BOOT COVER VINYL SOLE 19" TALL ELASTIC ANKLES AND LEG OPENING	· SIZES: ONE SIZE · PCS / CASE: 200 = 100 PAIRS · WEIGHT / CASE: 12 LB · DESIGN: ANSI · COLOR: WHITE, GRAY, YELLOW & ORANGE	
4020	LAB COAT NO POCKETS NO ELASTICS (WRISTS OPTIONAL) THREE FRONT SNAP CLOSURES	· SIZES: S - 4XL · PCS / CASE: 30 · WEIGHT / CASE: 6 LB · DESIGN: ANSI · COLOR: WHITE, GRAY, YELLOW & ORANGE	

^{*}This image is representative and may vary from actual product.



